



For more information,
please contact:

Rick Ligeikis

Phone: +1 304 523 4700
Cell: +1 864 314 9046
Fax: +1 304 523 4039
Home Fax: +1 864 225 5512
rligeikis@samincoinc.com

Ed McFall

Phone: +1 304 523 4700
Cell: +1 304 638 7994
emcfall@samincoinc.com

Kenny Boles

Phone: +1 239 561 1561
Cell: +1 304 634 3380
kboles@samincoinc.com



DriveStart | IGBT BASED MEDIUM VOLTAGE SOFT STARTER
UP TO 6.6KV 500A

EXPERIENCE THE EVOLUTION OF SOFT STARTERS THE FIRST OF ITS KIND IGBT BASED MEDIUM VOLTAGE SOFT STARTER

OPTIMIZED FOR APPLICATIONS THAT REQUIRE LOW STARTING CURRENT AND/OR A HIGH STARTING TORQUE

- Provides full torque during start
- Starts at nominal motor current or lower
- Enable motor starting from weak electrical networks
- Reduces motor heat at start enabling use of standard motors

SAVING COSTS, ENERGY AND SPACE WHILE MEETING TOP PERFORMANCE REQUIREMENTS


- Significantly lower price point than a Medium Voltage VFD while providing similar soft start and soft stop features
- Integrated bypass ensures no energy loss during operation, reducing energy waste and operational costs
- Peak demand reduction
- Streamlined design translating to at least 50% reduction in space requirements vs. a VFD with comparable performance

INDUSTRIES AND APPLICATIONS



WATER

- Water pumps
- Waste water pumps
- Booster pumps



OIL & GAS

- Compressors
- Oil pumps
- LNG pumps



MINING

- Fans and blowers
- Conveyor belts
- Ball mills



INDUSTRY

- Compressors
- Refrigeration chillers
- Mixers



MARINE

- Thrusters
- Ballast and fire-fighting pumps
- Injection pumps

For more information,
please contact:

Rick Ligeikis

Phone: +1 304 523 4700
Cell: +1 864 314 9046
Fax: +1 304 523 4039
Home Fax: +1 864 225 5512
rligeikis@samincoinc.com

Ed McFall

Phone: +1 304 523 4700
Cell: +1 304 638 7994
emcfall@samincoinc.com

Kenny Boles

Phone: +1 239 561 1561
Cell: +1 304 634 3380
kboles@samincoinc.com





DriveStart

TECHNICAL SPECIFICATIONS

- Input voltage - Up to 6.6kV 50/60Hz +10% -15%
- Power range - Up to 6.6kV, 5MW
- Line starting current - 10% to 120% of motor rated current
- Starting capacity - 100% of FLC at 50°C, unlimited number of starts per hour
- Starting torque - Up to 160% of motor rated torque
- Internal synchronization system (bypass), from DriveStart to line power and back
- Soft Start and Soft Stop
- Multi-start capabilities
- Electronic Potential Current Transformer (EPCT) voltage and current measurements via fiber optics
- Integrated data logger and wave form capture for all major system signals including current and voltage (Optional)
- Remote diagnostics and failure analysis (Optional)

HOW TO ORDER

Example:

DriveStart - 300A - 4.16kV - 115VAC - 115VAC - 3M - S

↓	↓	↓	↓	↓
Rated Current	Line Voltage	Control Voltage	Control Input Voltage	Options
		115VAC or 230VAC	24VDC, 24VAC, 115VAC, 230VAC, 110VDC, 125VDC, 220VDC	3M - Modbus MSS - Multi soft stop/start SDL - Solcon Data Logger

Medium Voltage Soft Starters

Product	Description	Current and Voltage Range
HRVS-DN	Digital, Heavy Duty	2300-15000V, up to 15MW
HRVS-DN MEGA	Digital, Heavy Duty, High Power	2300 - 15000V, 15-48 MW

Low Voltage Soft Starters

Product	Description	Current & Voltage Range	Bypass	Controlled Phases
RVS-DX	Digital, Standard Duty	8 - 170A, 220-600V	Internal	3-Phase
RVS-DXM	Digital, General Duty	210-1100A, 208 - 600V	Internal	3-Phase
RVS-DN	Digital, Heavy Duty	8 - 3000A, 230 - 1200V	External	3-Phase
RVS-AX	Analog	8 - 170A, 220-600V	Internal > 31 A	3-Phase
Solstart	Compact Analog	31-170A, 220 - 600V	Internal	2-Phase

Motor Protection

Product	Description	Monitors
MPS-3000	Full motor protection for medium voltage or large low voltage motors	All three phase currents, voltages and up to 10 RTD inputs
TPR6-14	RTD relay	Accepts up to 14 PT100 RTD inputs or thermistor inputs
MIP	Motor insulation protection system	Monitors MV or large LV motors. Provides status indication (alarm and trip)

MEETING YOUR NEEDS ACROSS INDUSTRIES



For more information,
please contact:

Kris Vance
Phone: +1 239 561 1561
Cell: +1 239 980 5983
Fax: +1 239 561 1502
kvance@samincoinc.com

Rick Ligeikis
Phone: +1 304 523 4700
Cell: +1 304 654 9054
Fax: +1 304 523 4039
Home Fax: +1 864 225 5512
rligeikis@samincoinc.com



Kenny Boles
Phone: +1 239 561 1561
Cell: +1 304 634 3380
kboles@samincoinc.com

Solcon Industries has been manufacturing solid state soft starters for over 30 years and is recognized throughout the world for their highly engineered solid state controls, protection products and world class service.

Solcon USA delivers this same high level of product, service and support to the North American market. Contact Solcon USA's industry experts for technical and sales assistance or call us to get the name of your local representative. Service and support is also available from Solcon partners located in more than 75 countries around the world.

250 West Kensing Drive, #300, Cranberry Township, PA 16066

T: +1 724.473.1301 | F: +1 724.473.9506 | E: sales@solconusa.com | W: www.solconusa.com